NSN 5905-01-454-5163

A001a0

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-454-5163

4.020 ohms Resistance Tolerance In Percent: -1.000/4-1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 250.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: Battween 0.167 inches and 0.207 inches Body Diameter: Between 0.498 inches and 0.612 inches Power Dissipation Rating In Watts: 3.000 free air Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: B1349-mil+-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1349-mil+-39007711 government specification Shelf Life: N/a	
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 250.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: Between 0.167 inches and 0.207 inches Body Diameter: Between 0.187 inches and 0.812 inches Power Dissipation Rating In Watts: 3.000 free air Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil+7.39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil+7-39007/11 government specification Shelf Life: No	Electrical Resistance:
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: Between 0.167 inches and 0.207 inches Body Length: Between 0.498 inches and 0.612 inches Power Dissipation Rating In Watts: 3.000 free air Unpackaged Unit Weight: 4.0 grams Syle Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a	
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0. Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: Between 0.167 inches and 0.207 inches Beddy Length: Between 0.167 inches and 0.207 inches Bedween 0.167 inches Auß inches and 0.612 inches Power Dissipation Rating In Watts: 3.000 free air Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 250.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Indicator: Established Reliability Fallure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: Between 0.167 inches and 0.207 inches Body Dameter: Between 0.167 inches and 0.207 inches Body Length: Between 0.498 inches and 0.612 inches Power Dissipation Rating In Watts: 3.000 free air Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 250.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: Between 0.167 inches and 0.207 inches Body Diameter: Between 0.187 inches and 0.612 inches Power Dissipation Rating In Watts: 3.000 free air Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 81349-milt-739007 specification (includes engineering type builletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-milt-739007/11 government specification Shelf Life: N/a	Ambient Tempurature In Deg Celsius At Full Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Faiture Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Boddy Diameter: Between 0.167 inches and 0.207 inches Boddy Diameter: Between 0.498 inches and 0.812 inches Power Dissipation Rating In Watts: 3.000 free air Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type builletins, brochures, etc., that reflect specification type data in specification format; excludes commencial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a	25.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: Between 0.167 inches and 0.207 inches Body Diameter: Between 0.167 inches and 0.812 inches Power Dissipation Rating in Watts: 3.000 free air Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: B1349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1349-mil-r-39007/11 government specification Shelf Life: N/a	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: Between 0.167 inches and 0.207 inches Body Length: Between 0.498 inches and 0.612 inches Power Dissipation Rating In Watts: 3.000 free air Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a	250.0
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: Between 0.167 inches and 0.207 inches Body Length: Between 0.498 inches and 0.612 inches Power Dissipation Rating In Watts: 3.000 free air Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: Bata9-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a	Inclosure Method:
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: Between 0.167 inches and 0.207 inches Body Length: Between 0.498 inches and 0.612 inches Power Dissipation Rating in Watts: 3.000 free air Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a Unit Of Measure:	Encapsulated
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: Between 0.167 inches and 0.207 inches Body Length: Between 0.498 inches and 0.612 inches Power Dissipation Rating In Watts: 3.000 free air Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a	Terminal Type:
Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: Between 0.167 inches and 0.207 inches Body Length: Between 0.498 inches and 0.612 inches Power Dissipation Rating In Watts: 3.000 free air Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a	Wire lead
Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: Between 0.167 inches and 0.207 inches Body Length: Between 0.498 inches and 0.612 inches Power Dissipation Rating In Watts: 3.000 free air Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a	Reliability Indicator:
Terminal Length: 1.500 inches Body Diameter: Between 0.167 inches and 0.207 inches Body Length: Between 0.498 inches and 0.612 inches Power Dissipation Rating In Watts: 3.000 free air Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life:	Established
Terminal Length: 1.500 inches Body Diameter: Between 0.167 inches and 0.207 inches Body Length: Between 0.498 inches and 0.612 inches Power Dissipation Rating In Watts: 3.000 free air Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life:	Reliability Failure Rate Level In Percent:
1.500 inches Body Diameter: Between 0.167 inches and 0.207 inches Body Length: Between 0.498 inches and 0.612 inches Power Dissipation Rating In Watts: 3.000 free air Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a	0.010
Body Diameter: Between 0.167 inches and 0.207 inches Body Length: Between 0.498 inches and 0.612 inches Power Dissipation Rating In Watts: 3.000 free air Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a	Terminal Length:
Between 0.167 inches and 0.207 inches Body Length: Between 0.498 inches and 0.612 inches Power Dissipation Rating In Watts: 3.000 free air Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a	1.500 inches
Between 0.498 inches and 0.612 inches Power Dissipation Rating In Watts: 3.000 free air Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a	Body Diameter:
Between 0.498 inches and 0.612 inches Power Dissipation Rating In Watts: 3.000 free air Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a	Between 0.167 inches and 0.207 inches
Power Dissipation Rating In Watts: 3.000 free air Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a	Body Length:
3.000 free air Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a	Between 0.498 inches and 0.612 inches
Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a	Power Dissipation Rating In Watts:
4.0 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a	3.000 free air
Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a	Unpackaged Unit Weight:
Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a	4.0 grams
Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a	Style Designator:
81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a	Axial terminal each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a	81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Specification Data: 81349-mil-r-39007/11 government specification Shelf Life: N/a	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
81349-mil-r-39007/11 government specification Shelf Life: N/a	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life: N/a	Specification Data:
N/a	81349-mil-r-39007/11 government specification
	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:
	
Demilitarization:	Demilitarization:
No	No
Fiig:	Fiig: