## NSN 5905-01-456-1113

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-456-1113

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:				
-300.0/+300.0				
Electrical Resistance:				
750.000 ohms				
Resistance Tolerance In Percent:				
-2.000/+2.000				
Ambient Tempurature In Deg Celsius At Full Rated Power:				
70.0				
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:				
125.0				
Tempurature Range Of Tempurature Coefficient In Deg Celsius:				
-55.0/+125.0				
Inclosure Method:				
Encapsulated				
Terminal Quantity:				
8				
Terminal Type:				
Pin				
Reliability Indicator:				
Not established				
Terminal Length:				
Between 0.125 inches and 0.150 inches				
Body Length:				
Between 0.760 inches and 0.798 inches				
Body Width:				
0.098 inches				
Body Height:				
Between 0.177 inches and 0.197 inches				
Schematic Diagram Designator:				
Isolated array				
Power Dissipation Rating In Watts:				
0.120 each resistor				
Identical Value Resistor Quantity:				
4 each resistor				
Style Designator:				
Single inline				
Test Data Document:				
81349-mil-prf-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification				
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain				
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).				
Specification Data:				

N/a

Shelf Life:

81349-mil-prf-83401/8 government specification

## NSN 5905-01-456-1113

Film Fixed Resistor Network - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-83401 spec.