## NSN 5905-01-456-1255

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-456-1255

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:  |
|--|
| -300.0/+300.0  |
| Electrical Resistance:   |
| 46.400 kilohms   |
| Resistance Tolerance In Percent:   |
| -1.000/+1.000  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 70.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 125.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:   |
| -55.0/+125.0   |
| Inclosure Method:  |
| Encapsulated   |
| Terminal Quantity:   |
| 6  |
| Terminal Type:   |
| Pin  |
| Reliability Indicator:   |
| Not established  |
| Terminal Length:   |
| Between 0.125 inches and 0.150 inches  |
| Body Length:   |
| Between 0.560 inches and 0.598 inches  |
| Body Width:  |
| 0.098 inches   |
| Body Height:   |
| Between 0.177 inches and 0.197 inches  |
| Schematic Diagram Designator:  |
| Ladder network   |
| Power Dissipation Rating In Watts:   |
| 0.120 each resistor  |
| Identical Value Resistor Quantity:   |
| 5 each resistor  |
| Style Designator:  |
| Single inline  |
| Test Data Document:  |
| 81349-mil-prf-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain            |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                              |
| Specification Data:  |

N/a

Shelf Life:

81349-mil-prf-83401/7 government specification

## NSN 5905-01-456-1255

Film Fixed Resistor Network - Page 2 of 2



|  | ι | Jn | it | Of | Measure: |
|--|---|----|----|----|----------|
|--|---|----|----|----|----------|

--

Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-83401 spec.