NSN 5905-01-456-2515

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-456-2515
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-5.0/+5.0 first temp coefficient
Electrical Resistance:
24.000 ohms
Resistance Tolerance In Percent:
-0.100/+0.100
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
175.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
+25.0/+125.0 temp range of first temp coefficient
Inclosure Method:
Encapsulated
Terminal Type:
Wire lead
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
1.000
Terminal Length:
Between 0.875 inches and 1.875 inches
Body Length:
0.336 inches
Body Width:
Between 0.290 inches and 0.320 inches
Body Height:
Between 0.095 inches and 0.120 inches
Power Dissipation Rating In Watts:
0.300 free air
Style Designator:
Terminals one edge
Test Data Document:
81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-prf-55182/9 government specification
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

NSN 5905-01-456-2515

Film Fixed Resistor - Page 2 of 2



Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-55182 spec.