Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-456-4325

## **Electrical Resistance:**

12.400 ohms

**Resistance Tolerance In Percent:** 

-1.000/+1.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

25.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

250.0

**Inclosure Method:** 

Encapsulated

Terminal Type:

Wire lead

**Reliability Indicator:** 

Established

Reliability Failure Rate Level In Percent:

1.000

Terminal Length:

1.500 inches

**Body Diameter:** 

Between 0.063 inches and 0.125 inches

**Body Length:** 

Between 0.375 inches and 0.437 inches

**Power Dissipation Rating In Watts:** 

2.000 free air

**Unpackaged Unit Weight:** 

1.0 grams

Style Designator:

Axial terminal each end

## **Test Data Document:**

81349-mil-prf-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-prf-39007/8 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-39007 spec.