NSN 5905-01-458-6854

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-458-6854 **Section Quantity:** 1 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.312 inches **Body Width:** 0.281 inches **Body Height:** 0.334 inches **Actuator Type:** Flush drive with slot-hole **End Application:** F15s **Screw Thread Diameter:** 0.110 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Lower adjacent side single row **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 10.0 kilohms single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Power Dissipation Rating Per Section In Watts:** 0.2 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Terminal Type And Quantity:**

3 tab, solder lug Shelf Life: N/a

NSN 5905-01-458-6854

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A002a0