## NSN 5905-01-461-1612

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-461-1612

| Electrical Resistance:   |
|--|
| 9.530 ohms   |
| Resistance Tolerance In Percent:   |
| -1.000/+1.000  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 25.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 250.0  |
| Inclosure Method:  |
| Encapsulated   |
| Terminal Type:   |
| Wire lead  |
| Reliability Indicator:   |
| Established  |
| Reliability Failure Rate Level In Percent:   |
| 0.100  |
| Terminal Length:   |
| 1.500 inches   |
| Body Diameter:   |
| Between 0.065 inches and 0.085 inches  |
| Body Length:   |
| Between 0.219 inches and 0.281 inches  |
| Power Dissipation Rating In Watts:   |
| 1.000 free air   |
| Unpackaged Unit Weight:  |
| 7.0 grams  |
| Style Designator:  |
| Axial terminal each end  |
| Test Data Document:  |
| 81349-mil-prf-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain            |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                              |
| Specification Data:  |
| 81349-mil-prf-39007/9 government specification   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |
| Fiig:  |
| - A00120   |

Mil-prf-39007 spec.

Mil-std (military Standard):