## NSN 5905-01-461-4055

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-461-4055 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.035 inches **Mounting Bushing Length:** 0.025 inches **Body Length:** 0.035 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 5000.0 ohms c and better flooring Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 70.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 7th secondary quality **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Special Features:** Manufacturer name cermet panel potentiometer; immersion sealed; lug terminals; slotted; 5000 ohm resistance; plain bushing 0.250 in. Long; linear taper type porm 10 pct **Terminal Type And Quantity:** 1 solder stud Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5905-01-461-4055

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0