## NSN 5905-01-462-9993

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-462-9993
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-100.0/+100.0
Electrical Resistance:
220.000 ohms
Resistance Tolerance In Percent:
-2.000/+2.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+125.0
Inclosure Method:
Encapsulated
Terminal Quantity:
6
Terminal Type:
Pin
Reliability Indicator:
Not established
Terminal Length:
Between 0.125 inches and 0.150 inches
Body Length:
Between 0.568 inches and 0.598 inches
Body Width:
0.098 inches
Body Height:
Between 0.332 inches and 0.350 inches
Schematic Diagram Designator:
Balanced ladder network
Power Dissipation Rating In Watts:
0.880 total network
Identical Value Resistor Quantity:
4 lowest resistance value
Style Designator:
Single inline
Test Data Document:
81349-mil-prf-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:** 

81349-mil-prf-83401/4 government specification

Shelf Life:

N/a

## NSN 5905-01-462-9993

Film Fixed Resistor Network - Page 2 of 2



		. ~				
ı	ını	t Of	· M	മമ	CII	re.

--

Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-83401 spec.