Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-463-1754

# Section Quantity:

2

Cylindrical servo mounted

#### **Pilot Diameter:**

**Body Style:** 

Between 15.850 millimeters and 15.875 millimeters

#### Pilot Length:

Between 1.5 millimeters and 1.7 millimeters

#### **Undercut Diameter:**

Between 21.8 millimeters and 22.6 millimeters

### **Undercut Width:**

1.6 millimeters

Angle Of Mounting Hole In Deg:

#### 15.9

Angle Between Centerlines Of Mounting Holes In Deg:

# 15.9

Shaft Length:

Between 8.7 millimeters and 10.3 millimeters

#### **Body Length:**

Between 39.6 millimeters and 40.1 millimeters

#### Mounting Lip Diameter:

Between 22.1 millimeters and 22.3 millimeters

#### Mounting Lip Depth:

Between 1.5 millimeters and 1.7 millimeters

#### Mounting Hole/stud Circle Diameter:

Between 15.850 millimeters and 15.875 millimeters

#### Shaft Style:

Round

Actuator Type:

Single shaft

#### Mounting Facility Quantity:

3

## Mounting Method:

Unthreaded hole

## **Electrical Resistance Per Section:**

10.0 kilohms all sections

# Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

## **Resistance Tolerance Per Section In Percent:**

-3.0/+3.0 all sections

Shelf Life:

N/a

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0