## NSN 5905-01-463-2186

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-463-2186

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:                                    |
|--|
| -100.0/+100.0  |
| Electrical Resistance:   |
| 470.000 ohms   |
| Resistance Tolerance In Percent:   |
| -2.000/+2.000  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 70.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:                                  |
| 150.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:                                     |
| -55.0/+125.0   |
| Inclosure Method:  |
| Encapsulated   |
| Terminal Quantity:   |
| 14   |
| Terminal Type:   |
| Tab, solder lug  |
| Reliability Indicator:   |
| Not established  |
| Body Length:   |
| 0.010 inches   |
| Body Width:  |
| Between 0.215 inches and 0.225 inches  |
| Body Height:   |
| Between 0.075 inches and 0.085 inches  |
| Power Dissipation Rating In Watts:   |
| 1.050 total network  |
| End Application:   |
| C-17a aircraft e/i fscm 91637  |
| Identical Value Resistor Quantity:   |
| 12 each resistor   |
| Special Features:  |
| S399 refers to a precoating that is applied to improve adhesion of molding compound to substrate |
| Style Designator:  |
| Dual inline  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |

## NSN 5905-01-463-2186

Film Fixed Resistor Network - Page 2 of 2



Fiig:

A001a0