NSN 5905-01-463-4482

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-463-4482

Section Quantity:
1
Body Style:
Rectangular w/bushing/slot mounted
Reliability Indicator:
Not established
Terminal Length:
0.500 inches
Shaft Diameter:
0.128 inches
Shaft Length:
0.250 inches
Mounting Bushing Length:
0.250 inches
Body Length:
Between 0.400 inches and 0.600 inches
Body Width:
0.300 inches
Body Height:
0.590 inches
Shaft Style:
Round, slotted
Contact Arm Electrical Off Position:
Fully cw
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
9000.0
Center To Center Distance Between Terminals:
0.200 inches
Fragility Factor:
Moderately rugged
Lateral Distance Between Mounting Hole Centers:
Between 0.513 inches and 0.526 inches
Screw Thread Diameter:
0.203 inches
Screw Thread Series Designator:
Unf
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:

NSN 5905-01-463-4482

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Location:
Rear end
Mounting Method:
Standard bushing
Features Provided:
Humidity proof
Cubic Measure:
0.106 cubic inches
Electrical Resistance Per Section:
2.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Power Dissipation Rating Per Section In Watts:
0.75 7th secondary quality
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Clutch
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Test Data Document:
80063-sm-a838760 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
3 pin
Specification Data:
Sm-a-838760-1 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0