NSN 5905-01-463-5675

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-463-5675 **Section Quantity: Body Style:** Rectangular **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 210.0 **Maximum Starting Torque:** 1.39 inch-ounces **Maximum Running Torque:** 1.39 inch-ounces **Maximum Stop Torque:** 4.17 inch-ounces **Fragility Factor:** Moderately delicate **End Application:** 6030-01-414-8582 **Mounting Method: Terminal Electrical Resistance Per Section:** 10.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 240.0 Resistance Tempurature Characteristic Range Per Section In Percent: -55.0/+125.0 -55 degrees celsius single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a

--

Unit Of Measure:

NSN 5905-01-463-5675

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



_		••	• -				
1	em		ゖっ	riz	2 †1	n	
_			ıιa	114	au	VII	١.

No

Fiig:

A002a0