# NSN 5905-01-463-5916

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-463-5916

## Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-50.0/+50.0

#### **Electrical Resistance:**

2.050 kilohms

#### **Resistance Tolerance In Percent:**

-1.000/+1.000

#### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 70.0

#### Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

## Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0

#### **Inclosure Method:**

Encapsulated

#### **Terminal Type:**

Wire lead

## Mil-std-1276 Wire Lead Type Designator:

С

# Reliability Indicator:

Established

# Reliability Failure Rate Level In Percent:

0.010

#### **Terminal Length:**

Between 0.984 inches and 1.516 inches

#### **Body Diameter:**

Between 0.058 inches and 0.074 inches

#### Body Length:

Between 0.130 inches and 0.170 inches

#### **Power Dissipation Rating In Watts:**

0.250 free air

#### **End Application:**

Aaq-15 mc130h e/i fscm 81349

#### Unpackaged Unit Weight:

0.3 grams

#### Style Designator:

Axial terminal each end

#### **Test Data Document:**

81349-mil-prf-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-prf-39017/5 government specification

# Shelf Life:

N/a

# NSN 5905-01-463-5916

Film Fixed Resistor - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-39017 spec.

