## NSN 5905-01-463-7186

**Section Quantity:** 

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-463-7186

ı
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.500 inches
Shaft Diameter:
Between 0.122 inches and 0.126 inches
Shaft Length:
0.625 inches
Mounting Bushing Length:
0.500 inches
Body Length:
Between 0.469 inches and 0.593 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
End Application:
A-10a egi mod
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear-bottom
Mounting Method:
Locking bushing
Features Provided:
Shaft seal
Electrical Resistance Per Section:
150.0 kilohms single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Standard Taper Curve Per Section:
A single section

## NSN 5905-01-463-7186

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0