## NSN 5905-01-464-1546

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-464-1546 **Section Quantity: Reliability Indicator:** Not established **Shaft Style:** Round, knurled **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 210.0 **Fragility Factor:** Extremely fragile **End Application:** 6625-01-443-0552 **Terminal Location:** Front-rear **Mounting Method: Terminal Electrical Resistance Per Section:** 2.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 240.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Function Conformity Per Section:** Single section stepped conformity **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug

Shelf Life: N/a

## NSN 5905-01-464-1546

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A002a0