## NSN 5905-01-464-2426

Film Fixed Resistor - Page 1 of 2

-10.0/+10.0

4.000 kilohms

**Electrical Resistance:** 

**Resistance Tolerance In Percent:** 



View Online at https://aerobasegroup.com/nsn/5905-01-464-2426

**Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:** 

-0.100/+0.100
Ambient Tempurature In Deg Celsius At Full Rated Power:
-125.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
175.0
Inclosure Method:
Encapsulated
Terminal Type:
Wire lead
Mil-std-1276 Wire Lead Type Designator:
C
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
1.000
Terminal Length:
1.375 inches
Body Length:
0.310 inches
Body Width:
0.320 inches
Body Height:
0.110 inches
Power Dissipation Rating In Watts:
0.300 free air
Style Designator:
Terminals one edge
Test Data Document:
81349 mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349 mil-prf-55182/9 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5905-01-464-2426

Film Fixed Resistor - Page 2 of 2



Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-55182 spec.