

View Online at <https://aerobasegroup.com/nsn/5905-01-464-5111>

Section Quantity:

1

Body Style:

Rectangular bushing mounted

Reliability Indicator:

Not established

Terminal Length:

Between 0.125 inches and 0.250 inches

First Flat Length:

0.312 inches

Flat Height:

0.218 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.250 inches

Mounting Bushing Length:

0.250 inches

Body Length:

0.781 inches

Body Width:

0.500 inches

Body Height:

0.500 inches

Shaft Style:

Round, flatted

Actuator Type:

Dual concentric

Center To Center Distance Between Terminals:

0.100 inches

End Application:

Used on navigation radar control panel interface pcb assembly

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear angled to bottom

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

10.0 kilohms single section

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-55.0/+150.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

Dust/splash resistant

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0