Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-465-2126

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-50.0/+50.0

#### **Electrical Resistance:**

1.270 kilohms

#### **Resistance Tolerance In Percent:**

-1.000/+1.000

#### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 70.0

#### Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

#### Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0

#### **Inclosure Method:**

Encapsulated

#### **Terminal Quantity:**

16

# **Terminal Type:**

Pin

# Reliability Indicator:

Not established

# Terminal Length:

Between 0.145 inches and 0.215 inches

#### **Body Length:**

Between 0.760 inches and 0.876 inches

#### **Body Width:**

Between 0.240 inches and 0.305 inches

#### **Body Height:**

0.180 inches

Schematic Diagram Designator:

Isolated array

#### **Power Dissipation Rating In Watts:**

1.600 total network

#### **End Application:**

B-1b cmup blk

#### **Identical Value Resistor Quantity:**

8 each resistor

# Style Designator:

Dual inline

#### **Test Data Document:**

81349-mil-prf-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-prf-83401/2 government specification

# NSN 5905-01-465-2126

Film Fixed Resistor Network - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0

# Mil-std (military Standard):

Mil-prf-83401 spec.

