

View Online at <https://aerobasegroup.com/nsn/5905-01-466-1475>

Section Quantity:

2

Body Style:

Rectangular bushing mounted

Reliability Indicator:

Not established

Terminal Length:

0.859 inches

First Flat Length:

0.250 inches

Flat Height:

0.104 inches

Shaft Diameter:

0.125 inches

Shaft Length:

Between 0.318 inches and 0.782 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.032 inches

Body Width:

0.032 inches

Body Height:

0.032 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.250 inches

Center To Center Distance Between Terminals:

0.100 inches

Fragility Factor:

Moderately rugged

End Application:

Communication

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Standard bushing

Center To Center Distance Between Terminal Rows:

0.300 inches

Features Provided:

Humidity proof

Electrical Resistance Per Section:

1.0 kilohms all sections

Center To Center Distance Between Center Terminal And Outside Terminal:

0.200 inches

Function Conformity Per Section:

All sections independent linearity

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Standard Taper Curve Per Section:

Z all sections

Terminal Type And Quantity:

6 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0