

View Online at <https://aerobasegroup.com/nsn/5905-01-466-1475>

**Section Quantity:**

2

**Body Style:**

Rectangular bushing mounted

**Reliability Indicator:**

Not established

**Terminal Length:**

0.859 inches

**First Flat Length:**

0.250 inches

**Flat Height:**

0.104 inches

**Shaft Diameter:**

0.125 inches

**Shaft Length:**

Between 0.318 inches and 0.782 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

0.032 inches

**Body Width:**

0.032 inches

**Body Height:**

0.032 inches

**Shaft Style:**

Round, flatted

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

0.250 inches

**Center To Center Distance Between Terminals:**

0.100 inches

**Fragility Factor:**

Moderately rugged

**End Application:**

Communication

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Lower adjacent side two rows

**Mounting Method:**

Standard bushing

**Center To Center Distance Between Terminal Rows:**

0.300 inches

**Features Provided:**

Humidity proof

**Electrical Resistance Per Section:**

1.0 kilohms all sections

**Center To Center Distance Between Center Terminal And Outside Terminal:**

0.200 inches

**Function Conformity Per Section:**

All sections independent linearity

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 all sections

**Standard Taper Curve Per Section:**

Z all sections

**Terminal Type And Quantity:**

6 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0