## NSN 5905-01-466-2574

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-466-2574

| Electrical Resistance:   |
|--|
| 630.000 ohms   |
| Resistance Tolerance In Percent:   |
| 0.200/+0.200   |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 70.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 150.0  |
| nclosure Method:   |
| Encapsulated   |
| Terminal Type:   |
| Wire lead  |
| Reliability Indicator:   |
| Established  |
| Reliability Failure Rate Level In Percent:   |
| 0.001  |
| Terminal Length:   |
| Between 1.375 inches and 0.625 inches  |
| Body Diameter:   |
| Between 0.082 inches and 0.098 inches  |
| Body Length:   |
| Between 0.204 inches and 0.231 inches  |
| Power Dissipation Rating In Watts:   |
| 0.250 free air   |
| Terminal Width:  |
| Between 0.023 inches and 0.027 inches  |
| Style Designator:  |
| Axial terminal each end  |
| Test Data Document:  |
| 31349-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental      |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  |
| Specification Data:  |
| 31349-mil-prf-39017/1 government specification   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| -  |
| Demilitarization:  |
| No   |
| Filg:  |
| A001a0   |

Mil-prf-39017 spec.

Mil-std (military Standard):