Nonprecision Wire Wound Variable Resistor - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5905-01-467-0481

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
Between 5.0 millimeters and 7.0 millimeters
Body Length:
8.0 millimeters
Body Width:
7.0 millimeters
Body Height:
6.6 millimeters
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
310.0
Center To Center Distance Between Terminals:
2.5 millimeters
Fragility Factor:
Moderately delicate
End Application:
6625-01-425-2551
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Terminal
Center To Center Distance Between Terminal Rows:
2.5 millimeters
Electrical Resistance Per Section:
200.000 ohms single section
Rotary Actuator Travel In Angular Deg:
310.0
Center To Center Distance Between Center Terminal And Outside Terminal:
5.0 millimeters
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
0.37 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section



Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0