Noninductive Wire Wound Fixed Resistor - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5905-01-467-2675

### **Electrical Resistance:**

1.500 kilohms

**Resistance Tolerance In Percent:** 

-1.000/+1.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

25.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

#### 250.0

**Inclosure Method:** 

Encapsulated

Terminal Type:

Wire lead

**Reliability Indicator:** 

Established

Reliability Failure Rate Level In Percent:

# 1.000

**Terminal Length:** 

1.500 inches

#### **Body Diameter:**

Between 0.167 inches and 0.207 inches

#### **Body Length:**

Between 0.498 inches and 0.612 inches

### **Power Dissipation Rating In Watts:**

3.000 free air

#### End Application:

Ot-17d/spg cw

### Style Designator:

Axial terminal each end

### **Test Data Document:**

-81349-mil-prf-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

-81349-mil-prf-39007/11 government specification

### Shelf Life:

N/a

### Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A001a0

## Mil-std (military Standard):

Mil-prf-39007 spec.

