## NSN 5905-01-467-6853

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-467-6853

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:   |
|---|
| -100.0/+100.0   |
| Electrical Resistance:  |
| 562.000 ohms  |
| Resistance Tolerance In Percent:  |
| -1.000/+1.000   |
| Ambient Tempurature In Deg Celsius At Full Rated Power:   |
| 70.0  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:   |
| 155.0   |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:  |
| -55.0/+155.0  |
| Inclosure Method:   |
| Uninclosed  |
| Terminal Type:  |
| Terminal type per body style  |
| Reliability Indicator:  |
| Not established   |
| Terminal Length:  |
| Between 0.2 millimeters and 0.6 millimeters   |
| Body Length:  |
| Between 1.9 millimeters and 2.1 millimeters   |
| Body Width:   |
| Between 1.15 millimeters and 1.35 millimeters   |
| Body Height:  |
| Between 0.45 millimeters and 0.65 millimeters   |
| Power Dissipation Rating In Watts:  |
| 0.125 free air  |
| End Application:  |
| Arc-164 apach   |
| Special Features:   |
| Tech data not authorized to be released outside of the us   |
| Precious Material And Location:   |
| Terminals palladium and terminals silver  |
| Style Designator:   |
| Termination pad each end  |
| Test Data Document:   |
| 37695-235186 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental         |

and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

--

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5905-01-467-6853

Film Fixed Resistor - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A001a0