Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-467-8168

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-300.0/+300.0

#### **Electrical Resistance:**

100.000 ohms

### **Resistance Tolerance In Percent:**

-1.000/+1.000

#### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 70.0

### Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

### Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0

#### **Inclosure Method:**

Encapsulated

#### **Terminal Quantity:**

10

### Terminal Type:

Pin

# **Reliability Indicator:**

Not established

# Terminal Length:

Between 0.125 inches and 0.150 inches

### **Body Length:**

Between 0.968 inches and 0.998 inches

### **Body Width:**

Between 0.050 inches and 0.103 inches

### **Body Height:**

Between 0.177 inches and 0.197 inches

### Schematic Diagram Designator:

Isolated array

### **Power Dissipation Rating In Watts:**

0.060 total network

### **Identical Value Resistor Quantity:**

5 each resistor

### **Unpackaged Unit Weight:**

1.6 grams

# Style Designator:

Single inline

### **Test Data Document:**

81349-mil-prf-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-prf-83401/9 government specification

# NSN 5905-01-467-8168

Film Fixed Resistor Network - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0

# Mil-std (military Standard):

Mil-prf-83401 spec.

