## NSN 5905-01-467-8177

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-467-8177

| view Offilite at https://defobasegroup.com/hsh/osos-of-407-0177  |
|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:  |
| -300.0/+300.0  |
| Electrical Resistance:   |
| 16.000 kilohms   |
| Resistance Tolerance In Percent:   |
| -2.000/+2.000  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 70.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 125.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:   |
| -55.0/+125.0   |
| Inclosure Method:  |
| Encapsulated   |
| Terminal Quantity:   |
| 10   |
| Terminal Type:   |
| Pin  |
| Reliability Indicator:   |
| Not established  |
| Terminal Length:   |
| Between 0.125 inches and 0.150 inches  |
| Body Length:   |
| Between 0.968 inches and 0.998 inches  |
| Body Width:  |
| Between 0.050 inches and 0.103 inches  |
| Body Height:   |
| Between 0.177 inches and 0.197 inches  |
| Schematic Diagram Designator:  |
| Isolated array   |
| Power Dissipation Rating In Watts:   |
| 0.060 total network  |
| Identical Value Resistor Quantity:   |
| 5 each resistor  |
| Unpackaged Unit Weight:  |
| 1.6 grams  |
| Style Designator:  |
| Single inline  |
| Test Data Document:  |
| 81349-mil-prf-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-prf-83401/9 government specification

## NSN 5905-01-467-8177

Film Fixed Resistor Network - Page 2 of 2



| Shelf Life:       |
|-------------------|
| N/a               |
| Unit Of Measure:  |
|                   |
| Demilitarization: |
|                   |
| No                |
| No Fiig:          |

Mil-std (military Standard):

Mil-prf-83401 spec.