Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-469-0169

## Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-100.0/+100.0

### **Electrical Resistance:**

332.000 ohms

## **Resistance Tolerance In Percent:**

-1.000/+1.000

## Ambient Tempurature In Deg Celsius At Full Rated Power:

## 70.0

### Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

## Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0

### **Inclosure Method:**

Encapsulated

### **Terminal Quantity:**

8

### **Terminal Type:**

Pin

## **Reliability Indicator:**

Not established

## **Terminal Length:**

Between 0.125 inches and 0.150 inches

## **Body Length:**

Between 0.768 inches and 0.798 inches

#### **Body Width:**

0.098 inches

#### **Body Height:**

Between 0.332 inches and 0.350 inches

## Schematic Diagram Designator:

Ladder network

#### **Power Dissipation Rating In Watts:**

1.400 total network

#### **Identical Value Resistor Quantity:**

7 each resistor

## Style Designator:

Single inline

## **Test Data Document:**

81349-mil-prf-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-prf-83401/4 government specification

# Shelf Life:

N/a

Film Fixed Resistor Network - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-83401 spec.