## NSN 5905-01-471-7316

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-471-7316

| Tempurature Coefficient Of Resistance in Ppm Per Deg Celsius:  |
|--|
| -100.0/+100.0  |
| Electrical Resistance:   |
| 30.000 ohms  |
| Resistance Tolerance In Percent:   |
| -2.000/+2.000  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 70.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 150.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:   |
| -55.0/+150.0   |
| Inclosure Method:  |
| Uninclosed   |
| Terminal Type:   |
| Terminal type per body style   |
| Reliability Indicator:   |
| Established  |
| Reliability Failure Rate Level In Percent:   |
| 0.100  |
| Terminal Length:   |
| Between 0.010 inches and 0.020 inches  |
| Body Length:   |
| Between 0.074 inches and 0.086 inches  |
| Body Width:  |
| Between 0.015 inches and 0.033 inches  |
| Body Height:   |
| Between 0.045 inches and 0.055 inches  |
| Power Dissipation Rating In Watts:   |
| 0.100 free air   |
| End Application:   |
| Alq172cont mo  |
| Style Designator:  |
| Termination pad each end   |
| Test Data Document:  |
| 81349-mil-prf-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain            |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                              |
| Specification Data:  |
| 81349-mil-prf-55342/6 government specification   |
| Shelf Life:  |
| N/a  |

--

**Unit Of Measure:** 

## NSN 5905-01-471-7316

Film Fixed Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-55342 spec.