

View Online at <https://aerobasegroup.com/nsn/5905-01-472-1735>

**Reliability Indicator:**

Not established

**Terminal Length:**

1.500 inches

**Body Length:**

0.250 inches

**Body Outside Diameter:**

Between 0.070 inches and 0.130 inches

**Terminal Diameter:**

Between 0.125 inches and 0.127 inches

**Maximum Power Dissipation Rating:**

200.00 milliwatts

**Ambient Temperature At Full Rated Power:**

125.0 degrees celsius

**Maximum Operating Temp:**

125.0 degrees celsius

**Thermal Time Constant In Seconds:**

25.0

**Power Dissipation Constant In Milliwatts Per Deg Celsius:**

2.0

**Temperature Points For Resistance Readings At Zero Power:**

75.0 degrees celsius 6th resistance-temperature point

**Zero Power Resistance At Specificationified Temp:**

2.0 kilohms 4th resistance-temperature point

**Resistance Tolerance At A Specificationified Temperature In Percent:**

-9.0/+9.0 6th resistance-temperature point

**Inclosure Type:**

Encapsulated

**Zero Power Resistance:**

2.000 kilohms

**Zero Power Resistance Tolerance In Percent At Reference Temp:**

-5.0/+5.0

**Style Designator:**

Sealed or coated bead

**Test Data Document:**

81349-mil-prf-23648 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 wire lead

**Specification Data:**

81349-mil-prf-23648/20 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A086a0

**Mil-std (military Standard):**

Mil-prf-23648 spec.