Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-472-7463

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.001
Terminal Length:
0.300 inches
Shaft Diameter:
Between 0.050 inches and 0.100 inches
Shaft Length:
0.080 inches
Body Length:
0.420 inches
Body Width:
Between 0.145 inches and 0.195 inches
Body Height:
Between 0.310 inches and 0.340 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Roller
Contact Arm Electrical Off Position:
Fully ccw
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
5400.0
Maximum Running Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
Between 0.180 inches and 0.220 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
10.0 percent, rated amperes c and better flooring

NSN 5905-01-472-7463

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg: 5400.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.090 mils and 0.110 centimeters Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 7th secondary quality **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Standard Taper Curve Per Section:** A single section **Special Features:** Nha an/apq170 rad **Test Data Document:** 81349-mil-prf-39035 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 pin **Specification Data:** 81349-mil-prf-39035/2 government specification Shelf Life: Unit Of Measure: **Demilitarization:** Fiig: A002a0 Mil-std (military Standard): Mil-prf-39035 spec.

N/a

No