NSN 5905-01-474-0472

Film Fixed Resistor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5905-01-474-0472 |
|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -50.0/+50.0 |
| Electrical Resistance: |
| 1.210 kilohms |
| Resistance Tolerance In Percent: |
| -1.000/+1.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 70.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 150.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+150.0 |
| Inclosure Method: |
| Uninclosed |
| Terminal Type: |
| Terminal type per body style |
| Reliability Indicator: |
| Established |
| Reliability Failure Rate Level In Percent: |
| 0.010 |
| Terminal Length: |
| Between 0.010 inches and 0.020 inches |
| Body Length: |
| Between 0.098 inches and 0.112 inches |
| Body Width: |
| Between 0.045 inches and 0.055 inches |
| Body Height: |
| Between 0.015 inches and 0.033 inches |
| Power Dissipation Rating In Watts: |
| 0.100 free air |
| Style Designator: |
| Termination pad each end |
| Test Data Document: |
| 81349-mil-prf-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-prf-55342/3 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

No

Demilitarization:

NSN 5905-01-474-0472

Film Fixed Resistor - Page 2 of 2



Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-55342 spec.