## NSN 5905-01-474-8807

Film Fixed Resistor - Page 1 of 2

-100.0 to 100.0

13.000 kilohms

-2.000 to 2.000

**Electrical Resistance:** 

**Resistance Tolerance In Percent:** 



View Online at https://aerobasegroup.com/nsn/5905-01-474-8807

**Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:** 

Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
150.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0 to 150.0
Inclosure Method:
Encapsulated
Terminal Type:
Wire lead
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.100
Terminal Length:
1.500 inches
Body Diameter:
0.138 inches
Body Length:
0.375 inches
Power Dissipation Rating In Watts:
0.500 free air
End Application:
1430-01-446-5321
Unpackaged Unit Weight:
0.750 grams
Style Designator:
Axial terminal each end
Test Data Document:
81349-mil-prf-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-prf-39017/2 government specification
Shelf Life:
N/a
Unit Of Measure:

## NSN 5905-01-474-8807

Film Fixed Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-39017 spec.