NSN 5905-01-475-0592

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-475-0592

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-300.0/+300.0
Electrical Resistance:
3.010 kilohms
Resistance Tolerance In Percent:
-1.000/+1.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+125.0
Inclosure Method:
Encapsulated
Terminal Quantity:
8
Terminal Type:
Pin
Reliability Indicator:
Not established
Terminal Length:
Between 0.125 inches and 0.150 inches
Body Length:
Between 0.768 inches and 0.798 inches
Body Width:
Between 0.050 inches and 0.103 inches
Body Height:
Between 0.332 inches and 0.350 inches
Schematic Diagram Designator:
Isolated array
Power Dissipation Rating In Watts:
0.800 total network
End Application:
5865-01-439-2738
Identical Value Resistor Quantity:
4 each resistor
Style Designator:
Single inline
Test Data Document:
81349-mil-prf-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-prf-83401/6 government specification

NSN 5905-01-475-0592

Film Fixed Resistor Network - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
No Fiig:

Mil-std (military Standard): Mil-prf-83401 spec.