## NSN 5905-01-475-6541

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-475-6541 **Section Quantity:** 1 **Body Style:** Rectangular w/bushing **Reliability Indicator:** Not established **Terminal Length:** 0.250 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.500 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.450 inches **Body Width:** 0.500 inches **Body Height:** 0.500 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Center To Center Distance Between Terminals:** 0.100 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Lower adjacent side single row **Mounting Method:** Standard bushing **Features Provided:** 

Hermetically sealed **Electrical Resistance Per Section:** 

5.0 kilohms single section

**Center To Center Distance Between Center Terminal And Outside Terminal:** 

0.100 inches

## NSN 5905-01-475-6541

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



## Power Dissipation Rating Per Section In Watts: 0.5 free air single section Resistance Tolerance Per Section In Percent: -20.0/+20.0 single section Terminal Type And Quantity: 3 pin Shelf Life: N/a Unit Of Measure: - Demilitarization: No

**Fiig:** A002a0