## NSN 5905-01-477-5464

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-477-5464

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius | : |
|--|---|
| -100 0 to 100 0  |   |

**Electrical Resistance:** 

16.900 kilohms

**Resistance Tolerance In Percent:** 

-1.000 to 1.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

125.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

175.0

**Tempurature Range Of Tempurature Coefficient In Deg Celsius:** 

-55.0 to 175.0

**Inclosure Method:** 

Encapsulated

**Terminal Type:** 

Wire lead

Mil-std-1276 Wire Lead Type Designator:

С

**Reliability Indicator:** 

Established

Reliability Failure Rate Level In Percent:

1.000

**Terminal Length:** 

Between 1.000 inches and 1.625 inches

**Body Diameter:** 

Between 0.078 inches and 0.140 inches

**Body Length:** 

Between 0.204 inches and 0.281 inches

**Power Dissipation Rating In Watts:** 

0.100 free air

**End Application:** 

Nav-8a/b/cdcn

**Unpackaged Unit Weight:** 

0.35 grams

**Style Designator:** 

Axial terminal each end

**Test Data Document:** 

81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:** 

81349-mil-prf-55182/1 government specification

Shelf Life:

N/a

## NSN 5905-01-477-5464

Film Fixed Resistor - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-55182 spec.