# NSN 5905-01-478-1757

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-478-1757

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-25.0/+25.0

#### **Electrical Resistance:**

14.300 kilohms

#### **Resistance Tolerance In Percent:**

-1.000/+1.000

#### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 125.0

#### Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

175.0

# Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+175.0

#### **Inclosure Method:**

Encapsulated

#### **Terminal Type:**

Wire lead

Mil-std-1276 Wire Lead Type Designator:

С

# **Reliability Indicator:**

Established

# Reliability Failure Rate Level In Percent:

1.000

#### Terminal Length:

Between 0.984 inches and 1.512 inches

#### **Body Diameter:**

Between 0.050 inches and 0.080 inches

#### Body Length:

Between 0.130 inches and 0.170 inches

#### **Power Dissipation Rating In Watts:**

0.050 free air

### End Application:

An/bsy-2 depo

#### Criticality Code Justification:

Agav

#### Style Designator:

Axial terminal each end

#### **Test Data Document:**

81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Shelf Life:

N/a

# NSN 5905-01-478-1757

Film Fixed Resistor - Page 2 of 2

Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-55182 spec.

