NSN 5905-01-478-2099

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-478-2099 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established First Flat Length: 1.563 inches Flat Height: 0.344 inches **Body Diameter:** 12.000 inches

0.375 inches **Shaft Length:** 2.000 inches

Mounting Bushing Length: 1.250 inches **Body Length:**

3.000 inches **Shaft Style:**

Shaft Diameter:

Round, flatted **Actuator Type:**

Single shaft

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Screw Thready Qty Per Inch (tpi):

20.0

Unc

Mounting Facility Quantity:

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Threaded hole

Electrical Resistance Per Section:

2.000 ohms single section

Power Dissipation Rating Per Section In Watts:

1000.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

NSN 5905-01-478-2099

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0