## NSN 5905-01-478-2099

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-478-2099 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established First Flat Length: 1.563 inches Flat Height: 0.344 inches **Body Diameter:** 12.000 inches

0.375 inches **Shaft Length:** 2.000 inches

**Mounting Bushing Length:** 1.250 inches **Body Length:** 

3.000 inches **Shaft Style:** 

**Shaft Diameter:** 

Round, flatted **Actuator Type:** 

Single shaft

**Screw Thread Diameter:** 

0.250 inches

**Screw Thread Series Designator:** 

Screw Thready Qty Per Inch (tpi):

20.0

Unc

**Mounting Facility Quantity:** 

**Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Threaded hole

**Electrical Resistance Per Section:** 

2.000 ohms single section

**Power Dissipation Rating Per Section In Watts:** 

1000.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

## NSN 5905-01-478-2099

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Standard Taper Curve Per Section |
|----------------------------------|
| A single section                 |
| Terminal Type And Quantity:      |
| 3 tab, solder lug                |
| Shelf Life:                      |
| N/a                              |
| Unit Of Measure:                 |
|                                  |
| Demilitarization:                |
| No                               |
|                                  |

Fiig: A002a0