NSN 5905-01-479-3573

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-479-3573

Tempurature Coefficient Of Resistance In Ppm Per Deg	Celsius:
--	----------

-100.0/+100.0

Electrical Resistance:

9.760 kilohms

Resistance Tolerance In Percent:

-1.000/+1.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

70.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

150.0

Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0 temp range of first temp coefficient

Inclosure Method:

Uninclosed

Terminal Type:

Terminal type per body style

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.010

Body Length:

Between 0.019 inches and 0.218 inches

Body Width:

Between 0.015 inches and 0.033 inches

Body Height:

Between 0.093 inches and 0.103 inches

Power Dissipation Rating In Watts:

0.800 free air

End Application:

First pbl; electronic componen

Criticality Code Justification:

Agav

Style Designator:

Termination pad each end

Test Data Document:

81349-mil-prf-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349 - mil-prf-55342/8 government specification

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5905-01-479-3573

Film Fixed Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-55342 spec.