# NSN 5905-01-480-1809

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-480-1809

## Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-25.0/+25.0

## **Electrical Resistance:**

221.000 ohms

## **Resistance Tolerance In Percent:**

-1.000/+1.000

## Ambient Tempurature In Deg Celsius At Full Rated Power:

### 125.0

## Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

175.0

## Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+175.0

## **Inclosure Method:**

Encapsulated

### **Terminal Type:**

Wire lead

## Mil-std-1276 Wire Lead Type Designator:

```
С
```

## **Reliability Indicator:**

Established

## Reliability Failure Rate Level In Percent:

0.100

## **Terminal Length:**

Between 0.984 inches and 1.512 inches

## **Body Diameter:**

Between 0.050 inches and 0.080 inches

## **Body Length:**

Between 0.130 inches and 0.170 inches

## **Power Dissipation Rating In Watts:**

0.050 free air

## End Application:

An/bsy-2 depo

## Criticality Code Justification:

Agav

## Style Designator:

Axial terminal each end

## **Test Data Document:**

81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Shelf Life:

N/a

# NSN 5905-01-480-1809

Film Fixed Resistor - Page 2 of 2

Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-55182 spec.

