Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



NSN 5905-01-480-6319 View Online at https://aerobasegroup.com/nsn/5905-01-480-6319 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Terminal Length:** 0.6 millimeters **Body Length:** Between 2.0 millimeters and 3.0 millimeters **Body Width:** 4.5 millimeters **Body Height:** 5.0 millimeters

**Actuator Type:** 

Flush drive with slot-hole

**Effective Electrical Rotation In Deg Angular Rotation:** 

210.0

**End Application:** 

Stv camera sy

**Terminal Location:** 

Right-left adjacent sides

**Mounting Method:** 

**Terminal** 

**Electrical Resistance Per Section:** 

200.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

240.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

**Power Dissipation Rating Per Section In Watts:** 

0.25 free air single section

**Resistance Tolerance Per Section In Percent:** 

-20.0/+20.0 single section

**Actuator Travel Control Feature:** 

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

**Standard Taper Curve Per Section:** 

A single section

## NSN 5905-01-480-6319

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0