Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-480-6345

New Online at https://aerobasegroup.com/nsi//3903-01-400-0345
Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
0.6 millimeters
Body Length:
Between 2.0 millimeters and 3.0 millimeters
Body Width:
4.5 millimeters
Body Height:
5.0 millimeters
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
210.0
End Application:
Stv camera sy
Terminal Location:
Right-left adjacent sides
Mounting Method:
Terminal
Electrical Resistance Per Section:
100.0 ohms single section
Rotary Actuator Travel In Angular Deg:
240.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section



## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A002a0