Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-481-4413

# Section Quantity:

1

Body Style: Cylindrical bushing mounted Reliability Indicator: Not established Body Diameter: Between 0.719 inches and 0.781 inches Shaft Diameter: Between 0.124 inches and 0.126 inches Shaft Length: Between 0.844 inches and 0.906 inches Mounting Bushing Length: 0.375 inches

Body Length:

Between 0.359 inches and 0.391 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Screw Thread Diameter:

0.250 inches

**Screw Thread Series Designator:** 

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

#### Mounting Method:

Standard bushing

**Features Provided:** 

Humidity proof

**Electrical Resistance Per Section:** 

25.0 ohms single section

#### **Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

### **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0