## NSN 5905-01-481-9867

Film Fixed Resistor - Page 1 of 1

Mil-std (military Standard):

Mil-prf-55182 spec.



View Online at https://aerobasegroup.com/nsn/5905-01-481-9867

Tempurature Coefficient Of Registence In Pam Per Deg Coloius
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -50.0/+50.0
Electrical Resistance:
1.200 kilohms
Resistance Tolerance In Percent:
-0.500/+0.500
Ambient Tempurature In Deg Celsius At Full Rated Power:
125.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
175.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+175.0 Inclosure Method:
Encapsulated Tarminal Types
Terminal Type: Wire lead
Reliability Indicator:  Established
Reliability Failure Rate Level In Percent:
0.010
Body Diameter:
0.250 inches
Body Length:
0.750 inches
Power Dissipation Rating In Watts:
0.500 free air
Style Designator:
Axial terminal each end
Test Data Document:
81349-mil-prf-55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-prf-55182 professional/industrial association specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A001a0