## NSN 5905-01-482-5061

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-482-5061

| Tempurature Coefficient Of Resistance In Ppm Per Deg | g Ceisius: |
|--|------------|
|--|------------|

-300.0/+300.0 first temp coefficient

**Electrical Resistance:** 

8.450 kilohms each resistor

**Resistance Tolerance In Percent:** 

-1.000/+1.000 each resistor

Ambient Tempurature In Deg Celsius At Full Rated Power:

70.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

150.0

**Tempurature Range Of Tempurature Coefficient In Deg Celsius:** 

-55.0/+150.0 temp range of first temp coefficient

**Inclosure Method:** 

Uninclosed

**Terminal Type:** 

Terminal type per body style

**Reliability Indicator:** 

Established

Reliability Failure Rate Level In Percent:

10.000

**Terminal Length:** 

Between 0.010 inches and 0.020 inches

**Body Length:** 

Between 0.148 inches and 0.162 inches

**Body Width:** 

Between 0.045 inches and 0.055 inches

**Body Height:** 

Between 0.015 inches and 0.033 inches

**Power Dissipation Rating In Watts:** 

0.150 free air

**End Application:** 

Iff

**Style Designator:** 

Termination pad each end

**Test Data Document:** 

81349-mil-prf-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:** 

81349-mil-prf-55342/4 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5905-01-482-5061

Film Fixed Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-55342 spec.