NSN 5905-01-482-7333

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-482-7333

Electrical Resistance:
511.000 ohms
Resistance Tolerance In Percent:
-1.000/+1.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
275.0
Inclosure Method:
Encased
Terminal Type:
Tab, solder lug
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.010
Terminal Length:
Between 0.250 inches and 0.374 inches
Body Length:
Between 0.688 inches and 0.812 inches
Body Width:
Between 0.376 inches and 0.500 inches
Body Height:
Between 0.375 inches and 0.437 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Between 0.552 inches and 0.572 inches
Power Dissipation Rating In Watts:
6.000 free air
Mounting Hole Size:
Between 0.089 inches and 0.099 inches
Unpackaged Unit Weight:
16.5 grams
Style Designator:
Axial terminal (s)
Test Data Document:
81349-mil-prf-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-prf-39009/2 government specification
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5905-01-482-7333

Inductive Wire Wound Fixed Resistor - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-39009 spec.