NSN 5905-01-482-9149

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-482-9149
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.7500 inches
Body Diameter:
Between 1.100 inches and 1.310 inches
Shaft Diameter:
Between 0.248 inches and 0.251 inches
Shaft Length:
Between 2.46875 inches and 2.53125 inches
Mounting Bushing Length:
Between 0.485 inches and 0.515 inches
Body Length:
Between 0.5500 inches and 0.7000 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

1000.0 ohms single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Terminal Type And Quantity:

5 solder stud

Specification Data:

81349-mil-r-19/2 government specification

NSN 5905-01-482-9149

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A002a0