## NSN 5905-01-484-5161

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-484-5161

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:                  |
|--|
| -50.0 to 50.0  |
| Electrical Resistance:   |
| 208.000 ohms   |
| Resistance Tolerance In Percent:   |
| -1.000 to 1.000  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:                        |
| 125.0  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:                |
| 175.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:                   |
| -55.0 to 175.0   |
| Inclosure Method:  |
| Encapsulated   |
| Terminal Type:   |
| Wire lead  |
| Mil-std-1276 Wire Lead Type Designator:  |
| С  |
| Reliability Indicator:   |
| Established  |
| Reliability Failure Rate Level In Percent:                                     |
| 0.001  |
| Terminal Length:   |
| 1.500 inches   |
| Body Diameter:   |
| 0.109 inches   |
| Body Length:   |
| 0.250 inches   |
| Power Dissipation Rating In Watts:   |
| 0.100 free air   |
| Unpackaged Unit Weight:  |
|  |
| 0.300 grams  |
| 0.300 grams Style Designator:  |
| -  |
| Style Designator:  |
| Style Designator: Axial terminal each end                                      |
| Style Designator:  Axial terminal each end  Shelf Life:                        |
| Style Designator: Axial terminal each end Shelf Life: N/a                      |
| Style Designator: Axial terminal each end Shelf Life: N/a                      |
| Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure: |

A001a0

## NSN 5905-01-484-5161

Film Fixed Resistor - Page 2 of 2



Mil-std (military Standard):

Mil-r-55182 spec.