
Noninductive Wire Wound Fixed Resistor - Page 1 of 2



## **Electrical Resistance:**

54.900 ohms

**Resistance Tolerance In Percent:** 

-1.000/+1.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

25.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

275.0

**Inclosure Method:** 

Encased

**Terminal Type:** 

Tab, solder lug

**Reactance Characteristic:** 

Inductive

**Reliability Indicator:** 

Established

Reliability Failure Rate Level In Percent:

0.010

**Body Length:** 

Between 1.000 inches and 1.124 inches

**Body Width:** 

Between 0.479 inches and 0.592 inches

**Body Height:** 

Between 0.063 inches and 0.125 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 0.709 inches and 0.729 inches

**Power Dissipation Rating In Watts:** 

8.000 free air

End Application:

Attack aircraft (av8b); dummy load electric

Mounting Hole Size:

Between 0.120 inches and 0.130 inches

Criticality Code Justification:

Agav

Style Designator:

Axial terminal (s)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No



## NSN 5905-01-485-1073

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



**Fiig:** A001a0